

## AKI Series Laboratory Incubator

- ❖ Microprocessor control
- ❖ Digital display setting and actual temperature
- ❖ Over temperature alarm PID self-tuning
- ❖ Digital display running time; stainless steel interior
- ❖ Electrocity Leakage Protection
- ❖ Glass inner door, hidden door lock
- ❖ Mechanical overheat protection, cut off heating sources
- ❖ Automatic alarm after operation
- ❖ Suitable for constant temperature tests, bacteria cultivation, breeding and ferment



MODEL		AKI-15	AKI-50	AKI-80	AKI-160	AKI-270
Chamber		15L	50L	80L	160L	270L
Power		150W	250W	300W	400W	600W
Temperature Range		Room Temperature 5-65°C				
Timer		0-9999min				
Temperature Resolution		0.1°C				
Temperature Fluctuation		±0.5°C				
Working Size mm/inch		250x250x250 10x10x10	350x350x410 14x14x16	400x400x500 16x16x20	500x500x650 20x20x26	600x600x750 24x24x30
Dimension mm/inch		380x370x580 15x14x23	480x470x740 19x18x29	530x530x840 21x21x33	640x630x1000 25x25x39	730x720x1090 29x28x43
Weight		51lb / 23kg	82lb / 37kg	106lb / 48kg	146lb / 66kg	198lb / 90kg
Cat No.	110V 60HZ	70231100	70231200	70231300	70231400	70231500
	220V 50HZ	70232100	70232200	70232300	70232400	70232500